WHIZ 2.0





The Whiz 2.0 Series combines sleek aesthetics with effective thermal management in a compact design, offering powerful downlighting from 15,000 to 41,900 lumens that meets DLC standards. It is available with an uplight configuration and compatible with our latest Archi-Color™ color-changing technologies.







B 490 lm



Housing	Ø16.2" × 4.4", 33 lbs		
Wattage	120W, 170W, 240W, 300W		
Dimming	0-10V 1%, TRIAC 1%, DALI 10%, DMX 0.1%		
ССТ	3000K, 3500K, 4500K, 5000K Tunable White, W+RGB		
Optics	25°, 40°, 60°, WIDE		
Lumen	STATIC WHITE 15,000 — 41,900 lm	ARCHI-COLOR™ W 16,525 Im R 510 Im G 4,000 Im	



Spurs Practice Facility | San Antonio, TX



Hagerty Garage + Social | Redmond, WA





A TRANSFORMATIVE NEW ADDITION

The Whiz 2.0 Bi-directional embodies architectural lighting excellence, building on the Whiz series' reputation for high performance and sophisticated design. This version introduces a new powerful, expressive indirect uplight, expanding the luminaire's versatility and elevating the potential for creative lighting solutions and aesthetic appeal.

- Direct & Indirect light combined delivers up to 48,750 lumens
- Archi-Color™ dynamic colors and white light combinations
- Control downlight and uplight separately with advanced dimming options

Housing	Ø18.9" × 4.57", 36 lbs			
Wattage	Downlight: 120 — 280W / Uplight: 30, 60W			
Dimming	0-10V 1%, DALI 10%, DMX 0.1%			
ССТ	3000K, 3500K, 4500K, 5000K Tunable White, W+RGB			
Optics	Downlight: 25°, 40°, 60°, Wide / Uplight: Wide			
Lumen	DOWNLIGHT 17,100 — 40,020 lm UPLIGHT 4,390 — 8,730 lm		RCHI-COLOR™ 16,515 Im 505 Im 4,000 Im 485 Im	

